


RCCN 日成VDRT/HF型耐高温无卤线槽 Halogen Free Wiring Duct



产品材质:采用无卤素硬质PCABS料制成,环保无污染,不含铅等有毒物。
 产品认证:美国UL 欧洲CE 欧洲环保RoHS,REACH,铁道阻燃低烟DIN5510。
 防火等级:UL94V-0,低烟微卤,遇火不燃烧,防火性及绝缘性特佳。
 产品构造:由槽底及槽盖组成,底槽两侧设有出线孔。
 颜色:灰色,乳白色,蓝色,黑色(可定制其它颜色,有起订量要求)
 工作温度:静态-40℃持续高温至110℃。
 使用方法:先将底槽固定,将所要配的线装入槽内,盖上槽盖即可。
 产品特性:1.反扣式槽盖与槽体设计组合后绝不脱落,且接合面平滑,不割伤手及擦损附近配线。
 2.配线槽110℃内不易断裂,变形,变色,装配省时便利。
 3.出线孔低、组合容易、拆卸简单、易于配线。

更多选择:量大可按需求生产所需规格或定制长度.例:VDR8080T/HF(L=1.7M)

Wide slot/finger design provides greater sidewall rigidity and can be used with a wide range of wire bundle sizes.

Certificates:UL:E306674 CE:EN50085 RoHS,REACH.

Made of rigid Halogen free PCABS

Work temperature:-40 °c to 110 °c

UL94 Flammability Rating of V-0

Provided with mounting holes

Available color:gray,white,blue,black and other special colors





Special length come with MOQ request

样式: 16mm-72mm宽

Style: Width from 16mm to 72mm

样式: 75mm-140mm宽

Style: Width from 75mm to 140mm



说明: 本系列16/35/45/65/75为非标产品。

This series is 16/35/45/65/75,they are not standard products

大小孔型号/Eu hole size : VDR4060F/614

单位/Unit:mm

型号 Item No.				宽 × 高 High X width W×H	孔宽 Slot width Q	齿宽 Finger width P	电线容量 以2.0平方计算 Wire capability/2.0sq	标准长度 Standard Length
灰色Gray RAL7030	乳白色White RAL7035	蓝色Blue RAL5015	黑色Black RAL9005					每支 2米
VDR2540T/HF	VDR2540TW/HF	VDR2540TE/HF	VDR2540TB/HF	25×40	8	10	20~35pcs	含槽底槽盖
VDR4040T/HF	VDR4040TW/HF	VDR4040TE/HF	VDR4040TB/HF	40×40	8	10	60~70pcs	
VDR6040T/HF	VDR6040TW/HF	VDR6040TE/HF	VDR6040TB/HF	60×40	8	10	100~115pcs	
VDR8040T/HF	VDR8040TW/HF	VDR8040TE/HF	VDR8040TB/HF	80×40	8	10	120~135pcs	
VDR2560T/HF	VDR2560TW/HF	VDR2560TE/HF	VDR2560TB/HF	25×60	8	10	40~50pcs	
VDR3060T/HF	VDR3060TW/HF	VDR3060TE/HF	VDR3060TB/HF	30×60	8	10	60~80pcs	
VDR3560T/HF	VDR3560TW/HF	VDR3560TE/HF	VDR3560TB/HF	35×60	8	10	90~105pcs	
VDR4060T/HF	VDR4060TW/HF	VDR4060TE/HF	VDR4060TB/HF	40×60	8	10	100~115pcs	
VDR4560T/HF	VDR4560TW/HF	VDR4560TE/HF	VDR4560TB/HF	45×60	8	10	110~125pcs	
VDR5060T/HF	VDR5060TW/HF	VDR5060TE/HF	VDR5060TB/HF	50×60	8	10	120~135pcs	
VDR6060T/HF	VDR6060TW/HF	VDR6060TE/HF	VDR6060TB/HF	60×60	8	10	120~135pcs	
VDR8060T/HF	VDR8060TW/HF	VDR8060TE/HF	VDR8060TB/HF	80×60	8	10	180~210pcs	
VDR10060T/HF	VDR10060TW/HF	VDR10060TE/HF	VDR10060TB/HF	100×60	8	10	240~290pcs	
VDR2580T/HF	VDR2580TW/HF	VDR2580TE/HF	VDR2580TB/HF	25×80	8	10	100~120pcs	
VDR3080T/HF	VDR3080TW/HF	VDR3080TE/HF	VDR3080TB/HF	30×80	8	10	110~125pcs	
VDR3580T/HF	VDR3580TW/HF	VDR3580TE/HF	VDR3580TB/HF	35×80	8	10	110~130pcs	
VDR4080T/HF	VDR4080TW/HF	VDR4080TE/HF	VDR4080TB/HF	40×80	8	10	140~160pcs	
VDR4580T/HF	VDR4580TW/HF	VDR4580TE/HF	VDR4580TB/HF	45×80	8	10	140~160pcs	
VDR5080T/HF	VDR5080TW/HF	VDR5080TE/HF	VDR5080TB/HF	50×80	8	10	160~180pcs	
VDR5580T/HF	VDR5580TW/HF	VDR5580TE/HF	VDR5580TB/HF	55×80	8	10	160~180pcs	
VDR6080T/HF	VDR6080TW/HF	VDR6080TE/HF	VDR6080TB/HF	60×80	8	10	180~210pcs	
VDR8080T/HF	VDR8080TW/HF	VDR8080TE/HF	VDR8080TB/HF	80×80	8	10	240~290pcs	
VDR10080T/HF	VDR10080TW/HF	VDR10080TE/HF	VDR10080TB/HF	100×80	8	10	260~350pcs	
VDR12080T/HF	VDR12080TW/HF	VDR12080TE/HF	VDR12080TB/HF	120×80	8	10	280~380pcs	
VDR25100T/HF	VDR25100TW/HF	VDR25100TE/HF	VDR25100TB/HF	25×100	8	10	110~160pcs	
VDR33100T/HF	VDR33100TW/HF	VDR33100TE/HF	VDR33100TB/HF	33×100	8	10	130~165pcs	
VDR40100T/HF	VDR40100TW/HF	VDR40100TE/HF	VDR40100TB/HF	40×100	8	10	130~175pcs	
VDR50100T/HF	VDR50100TW/HF	VDR50100TE/HF	VDR50100TB/HF	50×100	8	10	220~250pcs	
VDR60100T/HF	VDR60100TW/HF	VDR60100TE/HF	VDR60100TB/HF	60×100	8	10	240~290pcs	
VDR70100T/HF	VDR70100TW/HF	VDR70100TE/HF	VDR70100TB/HF	70×100	8	10	250~340pcs	
VDR75100T/HF	VDR75100TW/HF	VDR75100TE/HF	VDR75100TB/HF	75×100	8	10	260~350pcs	
VDR80100T/HF	VDR80100TW/HF	VDR80100TE/HF	VDR80100TB/HF	80×100	8	10	260~350pcs	
VDR100100T/HF	VDR100100TW/HF	VDR100100TE/HF	VDR100100TB/HF	100×100	8	10	300~400pcs	
VDR120100T/HF	VDR120100TW/HF	VDR120100TE/HF	VDR120100TB/HF	120×100	8	10	350~450pcs	