

RCCN 日成RF-HS收缩绝缘端子 RF-HS PE-Heat Shrinkable-Ring Terminals





铜套端子

型号	尺寸 DIMENSION				
Item No.	AWG mm ²	螺栓口直径 Dia. of bolt d2	W mm	L mm	颜色 Color
RFS1.25-3.5HS	22-16 0.5-1.5	3.7mm	5.7	25.0	红 Red
RFL1.25-4HS		4.3mm	8.0	28.5	
RF1.25-5HS		5.3mm	8.0	28.5	
RF1.25-6HS		6.5mm	11.6	34.5	
RF1.25-8HS		8.4mm	11.6	34.5	
RF1.25-10HS		10.5mm	13.6	37.5	
RFS2-3.5HS	16-14 1.5-2.5	3.7mm	6.6	26.5	蓝 Blue
RFL2-4HS		4.3mm	8.5	30.5	
RFL2-5HS		5.3mm	9.5	30.5	
RF2-6HS		6.5mm	12.0	35.5	
RF2-8HS		8.4mm	12.0	35.5	
RF2-10HS		10.5mm	14	37.5	
RFL5.5-4HS	12-10 4-6	4.3mm	9.5	26.5	黄 yellow
RF5.5-5HS		5.3mm	9.5	26.5	
RF5.5-6HS		6.5mm	12.0	31	
RF5.5-8HS		8.4mm	15.0	33.7	
RF5.5-10HS		10.5mm	15.0	33.7	
RF5.5-12HS		13.0mm	19.2	38.1	

型号	尺寸 DIMENSION				
Item No.	AWG mm ²	螺栓口直径 Dia. of bolt d2	W mm	L mm	颜色 Color
RFS1.25-3.5HD	22-16 0.5-1.5	3.7mm	5.7	25.0	红 Red
RFL1.25-4HD		4.3mm	8.0	28.5	
RF1.25-5HD		5.3mm	8.0	28.5	
RF1.25-6HD		6.5mm	11.6	34.5	
RF1.25-8HD		8.4mm	11.6	34.5	
RF1.25-10HD		10.5mm	13.6	37.5	
RFS2-3.5HD	16-14 1.5-2.5	3.7mm	6.6	26.5	蓝 Blue
RFL2-4HD		4.3mm	8.5	30.5	
RFL2-5HD		5.3mm	9.5	30.5	
RF2-6HD		6.5mm	12.0	35.5	
RF2-8HD		8.4mm	12.0	35.5	
RF2-10HD		10.5mm	14	37.5	
RFL5.5-4HD	12-10 4-6	4.3mm	9.5	26.5	黄 yellow
RF5.5-5HD		5.3mm	9.5	26.5	
RF5.5-6HD		6.5mm	12.0	31	
RF5.5-8HD		8.4mm	15.0	33.7	
RF5.5-10HD		10.5mm	15.0	33.7	
RF5.5-12HD		13.0mm	19.2	38.1	

RCCN 日成BHS型收缩中间端子 Butt Splice Heat Shrinkable



型号	导线截面 Insulated square		尺寸 DIMENSION			最大 电流 Imax	绝缘套颜色 INSULATION Color
Item No.	A.W.G	mm ²	d φ mm	L mm			
BHS-1.25	22-16	0.5-1.5	1.7	36.0		19A	红/Red
BHS-2.0	16-14	1.5-2.5	2.3	36.0		27A	蓝/Blue
BHS-5.5	12-10	4-6	3.4	41.0		48A	黄/Yellow

